Mini Converter SDI to Audio 4K



Mini Converter SDI to Audio 4K includes everything you need to de-embed 4 channels of analog audio or 8 channels of AES/EBU digital audio from any SDI video connection. Now you can access the audio in any SDI video connection for output to a massive range of audio equipment such as audio mixers, analog broadcast decks, audio monitors and more!

$405

Connections

SDI Video Inputs
1 x SD, HD or 6G-SDI. 1 x ALT SDI Input for automatic switch over if main input fails.

SDI Video Outputs
1 x SDI Video Loop Output.

SDI Redundant Inputs
Automatically switches over if main SDI input is lost.

Analog Audio Outputs
4 channels of professional balanced analog audio with standard 1/4 inch jack connections.

Digital Audio Outputs
8 channels of professional balanced digital with standard 1/4 inch jack connections.

Multi Rate Support
Auto detection SD, HD or 6G-SDI.

Updates and Configuration
USB

Reclocking
Yes



Standards

SD Video Standards
525i59.94 NTSC, 625i50 PAL

HD Video Standards
720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30, 1080i50, 1080i59.94, 1080i60

2K Video Standards
2K DCI 23.98p, 2K DCI 24p, 2K DCI 25p, 2K DCI 23.98PsF, 2K DCI 24PsF, 2K DCI 25PsF

Ultra HD Video Standards
2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30

4K Video Standards
4K DCI 23.98p, 4K DCI 24p, 4K DCI 25p

SDI Compliance
SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE ST-2081, ITU-R BT.656 and ITU-R BT.601

SDI Video Rates
SDI video inputs are automatically detected between standard definition and high definition.

SDI Video Sampling
4:2:2, 4:4:4

SDI Audio Sampling
Television standard sample rate of 48 kHz and 24 bit.

SDI Color Precision
4:2:2, 4:4:4

SDI Color Space
YUV, RGB

SDI Auto Switching
Automatically selects between SD, HD, 3G and 6G-SDI.

Software

Software Control
Mac™ and Windows™ software upgrade via USB.

Internal Software Upgrade
Via included updater application.

Operating Systems



Mac 10.15 Catalina,
Mac 11.1 Big Sur or later.



Windows 10, 64-bit.

Settings Control

Mini Switches or USB software.

Power Requirements

Power Supply
+12V universal power supply included with international socket adapters for most countries. Cable tie point.

Power Consumption
5.52 Watts

Operational Voltage Range
12V - 31V DC

Physical Specifications



Environmental Specifications

Operating temperature
0° to 40° C (32° to 104° F)

Storage temperature
-20° to 45° C (-4° to 113° F)

Relative Humidity
0% to 90% non-condensing

What's Included

Mini Converter SDI to Audio 4K
12V universal power supply with international socket adapters

Warranty

3 Year Limited Manufacturer’s Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2026, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. Privacy Policy

Blackmagic Design Authorized Reseller