Teranex Mini SDI to Analog 12G



Convert from 12G-SDI to Analog. Use SD, HD, 6G and 12G-SDI rates and convert to analog video output. Built in down converter lets you connect Ultra HD sources to component video equipment in SD or HD. Allows you to connect analog equipment including Betacam SP, VHS, and video monitors.

$665

Connections

SDI Video Inputs
1 x 12G-SDI SD/HD/2K/4K auto switching.

SDI Video Outputs
1 x 12G-SDI loop output.

Analog Video Outputs
Composite, Y/C or Component.

Analog Audio Outputs
2 channels professional balanced analog audio via XLR connectors. Right XLR can be configured for timecode output.


Digital Audio Outputs
4 channels professional 110Ω balanced digital audio via XLR connectors. Right XLR can be configured for timecode output.

Embedded Audio Support
16 channels.

Multi Rate Support
Automatic switching between SD/HD/2K and 4K.

Updates and Configuration
USB or Ethernet.

Reclocking
Yes



Standards

SD Video Standards
525i59.94 NTSC, 625i50 PAL

HD Video Standards
720p50, 720p59.94, 720p60
1080i50, 1080i59.94, 1080i60
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60
1080PsF23.98, 1080PsF24,
1080PsF25, 1080PsF29.97, 1080PsF30

2K Video Standards
2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI
2KPsF23.98 DCI, 2KPsF24 DCI,
2KPsF25 DCI

Ultra HD Video Standards
2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

4K Video Standards
4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI

SDI Compliance
SMPTE 259M, SMPTE 292M,
SMPTE 296M, SMPTE 372M,
SMPTE 424M, SMPTE 425M
level A and B, SMPTE 2081-1,
SMPTE 2081-10, SMPTE 2082-1 and
SMPTE 2082-10

SDI Video Rates
SDI video connections are auto switching between standard definition SDI, high definition level A and level B 3G-SDI, 6G-SDI, and 12G-SDI.

SDI Video Sampling
4:2:2 and 4:4:4

SDI Audio Sampling
Television standard sample rate of 48 kHz and 24-bit.

SDI Color Precision
4:2:2 and 4:4:4

SDI Color Space
YUV

Analog Video Standards
525i59.94 NTSC, 625i50 PAL

Analog Color Space
REC 601, REC 709

Analog Color Precision
YUV 4:2:2 and RGB 4:4:4 in HD, 2K and 4K.

Format Conversion

HD down conversion

Software

Software Control
Mac™ and Windows™ software upgrade via USB and Ethernet.

Internal Software Upgrade
Via included updater application.

Operating Systems



Mac 10.15 Catalina,
Mac 11.1 Big Sur or later.

Windows 10, 64-bit.

Settings Control

Basic Settings Control
Mini Switches, USB and Ethernet via free software utility.

Optional Front Panel Control
Front mounted Smart Panel with LCD, rotary knob and six settings buttons

Power Requirements

Power Supply
1 x built-in international AC power supply with IEC C14 inlet. IEC Power cable required. 100 - 240V AC Input.

Power Over Ethernet
Can be powered via 48V DC using PoE+ (power over ethernet).

Power Consumption
16 Watts

Operational Voltage Range
100 - 240V AC

Physical Specifications



Environmental Specifications

Operating Temperature
0° to 40°C (32° to 104°F)

Storage Temperature
-20° to 60°C (-4° to 140°F)

Relative Humidity
0% to 90% non-condensing

What's Included

Teranex Mini SDI to Analog 12G
Welcome wallet with QR code for software download

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2026, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. Privacy Policy

Blackmagic Design Authorized Reseller